Request for Proposal (RFP # 19-01 SCBA)

Addendum #2

(January 7, 2020)

Dear Respondents:

The following addendum supersedes information contained in the RFP to the extent referenced.

This Addendum forms part of the RFP documents and will be subject to all of the conditions set out in the contract conditions. Acknowledge receipt of this Addendum in the space provided on the Submission Form when bidding.

This Addendum # 2 contains 3 pages.

Appendix D – RFP Particulars

Please note the change to Annex F "Mandatory Technical Requirements"

**END OF ADDENDUM #2** 

Note: Amendment/addenda will be posted at <a href="https://www.gov.bm/procurement-notices">https://www.gov.bm/procurement-notices</a>. Respondents should visit the Government Portal website on a regular basis during the Procurement process.

Requirements	Meets Requirement	Does Not Meet Requirement	Exception/Explanation
NFPA Standard:	,		
All requirements of NFPA 1981			
Standard on Open-Circuit Self			
Contained Breathing			
Apparatus for emergency services 2018			
SCBA Model:			
The proposed SCBA model and face piece must be the latest model offered by the manufacturer.			
Face piece:			
Face piece will be offered in multiple			
sizes			
Voice Amplification:			
While SCBA is worn, every user will			
have voice amplification capabilities.			
Cylinder:			
All SCBA bottles in the proposal will			
be 4500psi, carbon fiber cylinders.			
All cylinders shall be adaptable to fit current SCBA fill stations			
Backframe:			
The SCBA back frame will be rigid			
and made of a composite or metal			
material for strength			
and durability.			
Cylinder Retention:			
All carbon fiber cylinders will be			
attached onto the SCBA back frame			
with a metal locking band, or	1		
webbing style strap and lock.			
Indicator lights:		· · · · · · · · · · · · · · · · ·	
All operation indicator lights will be			
visible to the user.			
Power Supply:			
The energy cells will either be			
rechargeable or disposable			
Waist belt/Lumbar:			
(a).For quick removal, the waist			
strap must be a seatbelt style, quick			
release buckle. (b) With			
consideration to user comfort, the			

lumbar section will be of a "swivel"		
type.		
Shoulder straps:		
Shoulder straps should connect to		
the back frame, not the waist strap,		
Shoulder straps should be field removable in order to be cleaned		
Shoulder gauge:		*
The shoulder air pressure		
gauge/PASS alarm will be of digital		
or pneumatic display design.		
Buddy Breathing:		
The buddy breather system should		
be secured to the back frame or		
lower harness with		
a heavy duty pouch.		
Warranty:		
A minimum of a 15 year warranty is		
required on all components included		
in the SCBA system (except		
consumables).		
	 	I .